

NGTC-2000 Digital Signal Processor

The NGTC-2000 is a Dante™ enabled digital signal processor with flexible I/O for the NEXGENTEC AUDIO distribution solution.

The NGTC-2000 is capable of simultaneously transmitting and receiving up to 64 channels of Dante™ audio (64 x 64) and has a completely flexible DSP design platform.

The NGTC-2000 can be easily interfaced with 3rd party control systems via the network. It can also be used with the NGTC-SDM, the software defined Dante™ matrix and monitoring device to deliver a virtually unlimited audio matrix system.

The nexgentec DSP super modules enable efficient design and deployment of the NGTC audio network system, featuring the highest levels of functionality and performance.



Key Features

- 4 Versatile option card slots
- Configurable signal processing
- Rich palette of processing and logic objects, nexgentec DSP super modules
- Dante™ audio, 64 x 64 audio input / output channels per device
- Redundant Dante™ ports (PRIM / SEC)
- LAN port for control
- RS232 port
- Informative front panel display
- 8 Logic inputs (or 4 analog control inputs) and 8 logic outputs
- Interface kit for third party control system integration

Power and Dimensions

Mains Voltage:	100 - 240 VAC, 50 / 60 Hz
Power Consumption:	< 45 VA
BTU Rating:	< 200 BTU / hr
Operation Temperature Range:	5° to 30°C
Dimensions (H x W x D):	480 mm x 241 mm x 43.7 mm – 1 U
Weight:	5.9 kg

NGTC-2000 Digital Signal Processor

Technical Specifications

- Front Panel Led Indicators: signal present, LCD display, data activity
- Control Ports: 8 logic inputs and 8 logic outputs
- Control Input Voltage: 0 to 3.3 VDC
- Control Input Impedance: 4.7 k Ω to + 5 V (2 - wire mode), > 1 M Ω (3 - wire mode)
- Logic Output Voltage: 0 or + 5 V unloaded
- Logic Output Impedance: 440 Ω s
- Logic Output Current: 10 mA source, 60 mA sink

- Watchdog Output: Phoenix / Combicon connector for failsafe control
- Opto Output Current: 14 mA maximum
- Withstanding Voltage: 80 V maximum (Off)
- Series Impedance: 220 Ω (isolated)
- Control Network: RJ45 Ethernet connector
- Maximum Cable Length: 100 m / 300 ft, category 5 / 6 / 7

- Digital Audio Bus: 2 x RJ45 Ethernet connectors
- Maximum Cable Length: 100 m / 300 ft, category 5 / 6 / 7
- Maximum Number of Nodes: 60
- Latency per Node: 4 (+/-1) Fs

- Dante™ Audio Network: 2 x RJ45 connectors
- Maximum Cable Length: 100 m / 300 ft, category 5 / 6 / 7