

NGTC-CRBIBOB AES67 Bluetooth® and TV Interface

The NGTC-CRBIBOB combines the NGTC-TVI2.0 and the NGTC-BTI in one small box and has, in addition, 2 channel analog audio in and 2 channel analog audio out.

Like the NGTC-TVI2.0, it is a multiformat digital audio interface that converts coaxial or TOSLINK signals to 2 channel audio on AES67.

In addition, like the NGTC-BTI, it also is a universal Bluetooth® AES67 enabled audio interface for the NEXGENTEC AUDIO distribution solution.

The NGTC-CRBIBOB features an API for navigation, configuration and management of the Bluetooth® interface.

The nexgentec DSP super modules by Genesis Technologies™ enable efficient design and deployment of NGTC audio network system featuring the highest levels of functionality and performance.



Key Features

- Bluetooth® audio V5
- Bluetooth® sink or source mode
- Similar feature set as the NGTC-BTI
- TOSLINK or coax digital audio inputs
- Supports all audio formats
- Similar feature set as the NGTC-TVI2.0
- 2 Ch analog audio input and output
- Management API, LAN API interface
- AES67, LAN audio port
- PoE powered

Power and Dimensions

Mains voltage:	PoE on AES67 port
Power consumption:	< 6 Watt
BTU rating:	< 22 BTU / hr
Operation temperature range:	5° to 30°C
Dimensions (H x W x D):	35 mm x 109 mm x 103 mm
Weight:	< 0.2 kg